



# Sand Pro<sup>®</sup> 2040Z

INFIELD GROOMER

## FEATURES

- *Kawasaki 12.2 hp (9.1 kW) gasoline, v-twin engine*
- *Integrated nail drag and flex groomer for one-pass grooming*
- *Power steering via independent control sticks*
- *Unitized transmission minimizes hydraulic lines and connections*
- *Transport speed up to 12 mph*
- *Hydraulic-powered groomer lift*
- *Two-post fixed ROPS, ISO/DIS 21299.2 certified*



*The Toro Sand Pro delivers true one-pass grooming.*

## Another industry first in infield maintenance.

The all-new Sand Pro 2040Z infield groomer is unlike anything else in the marketplace – a zero-turn infield groomer delivering unmatched maneuverability and productivity.

This unique machine with its exclusive nail drag/flex groomer is the perfect solution for daily infield grooming. The nimble Sand Pro 2040Z will save you valuable time in your workday, improving infield surface playability and consistency.

[toro.com/sandpro](http://toro.com/sandpro)



SAND PRO 2040Z, MODEL 08706																					
<b>ENGINE</b>	Kawasaki 2 cylinder, air cooled, gasoline engine; Gross HP 13.6 HP (10.1 kW), Governed HP 12.2 HP (9.1 kW) @ 2400 rpm; Max torque 27.3 ft-lbs (37.0 Nm) @1800 rpm; Displacement 36.7 cu-in. (603 cc); Oil capacity w/filter 1.7 qts. w/filter (1.5 w/o filter); Oil Filter External, spin-on																				
<b>AIR CLEANER SYSTEM</b>	Heavy duty single stage cyclonic air filter with replacement element																				
<b>FUEL CAPACITY</b>	4.5 gals (17 liters) of unleaded gas (maximum 10% ethanol)																				
<b>TRACTION DRIVE</b>	Belt driven independent infinitely variable unitized transmission, with automatic tensioning system.																				
<b>HYDRAULIC OIL</b>	Factory fill Mobil fluid 424 tractor transmission fluid; Left hand transmission section: 3.1 qt (3.25 liters); Right hand transmission section: 3.55 qt (3.75 liters)																				
<b>GROUND SPEED</b>	Forward 0-12 mph (0-19.3 km/h), Reverse 0-4 mph (0-6.4 km/h). See Speed Limiter Kits below for additional information.																				
<b>TIRES/WHEELS</b>	Drive Wheels 25x12- 9, 3 ply rating pneumatic tubeless demountable with a Turf Tamer (knobby) tread. Front Wheel 16x7.5-8 4 ply rating pneumatic tubeless demountable with turf traction tread. Recommended tire pressure: 7 psi all tires																				
<b>MAIN FRAME</b>	Rectangular structured steel tube and high strength steel plate welded construction.																				
<b>BRAKES</b>	Twin levers with dynamic braking through hydrostatic transmission. Hand actuated parking brake lever that controls two integral wet disc brakes contained within transmission.																				
<b>STEERING</b>	Power steering, controlled through two independent control sticks with integrated dampeners. Min. turning radius: 0 in (0 cm)																				
<b>CONTROLS/GAUGES</b>	Ignition: Off/Run/Start; Throttle: Low - High Idle; Choke: Open /Closes choke plate; Parking Brake: Off - On LCD logic cluster includes hour meter and safety interlocks for operator presence, neutral and parking brake.																				
<b>REAR ATTACHMENT HYDRAULIC LIFT</b>	Raise/Lower switch mounted at end of right handle.																				
<b>SEAT</b>	High back cushion vinyl seat with drain hole, integrated armrest and retractable seat belt; adjustment is 4 inches fore and aft.																				
<b>ROPS</b>	Two post fixed ROPS, certified per ISO/DIS 21299.2 specifications																				
<b>STORAGE</b>	Built-in cup holder, rake holder and personal storage reached from seat.																				
<b>ELECTRICAL FEATURES</b>	12-volt system, 20-amp alternator at 3,600 rpm. Battery Voltage is displayed when key switch is moved from off to run (Low Battery LED will illuminate if key voltage is less than 12.3V in run position)																				
<b>SOUND LEVEL</b>	88 dBA (Operator Ear)																				
<b>DIMENSIONS/WEIGHT</b>	<table border="1"> <thead> <tr> <th></th> <th>with Flex Tooth Rake</th> <th>with Nail Drag</th> <th></th> </tr> </thead> <tbody> <tr> <td><b>Length:</b></td> <td>89.0 in (226 cm)</td> <td>84.8 in (215 cm)</td> <td rowspan="5"><b>Wheelbase:</b> 58.0 in (147 cm) <b>Tread width (to centerline of tire):</b> 46.9 in (119 cm)</td> </tr> <tr> <td><b>Width:</b></td> <td>84.0 in (213 cm)</td> <td>71.5 in (182 cm)</td> </tr> <tr> <td><b>Overall Height:</b></td> <td>73.0 in (185 cm)</td> <td>73.0 in (185 cm)</td> </tr> <tr> <td><b>Weight:</b></td> <td>920 lbs (417 kg)</td> <td>970 lbs (439 kg)</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table>		with Flex Tooth Rake	with Nail Drag		<b>Length:</b>	89.0 in (226 cm)	84.8 in (215 cm)	<b>Wheelbase:</b> 58.0 in (147 cm) <b>Tread width (to centerline of tire):</b> 46.9 in (119 cm)	<b>Width:</b>	84.0 in (213 cm)	71.5 in (182 cm)	<b>Overall Height:</b>	73.0 in (185 cm)	73.0 in (185 cm)	<b>Weight:</b>	920 lbs (417 kg)	970 lbs (439 kg)			
	with Flex Tooth Rake	with Nail Drag																			
<b>Length:</b>	89.0 in (226 cm)	84.8 in (215 cm)	<b>Wheelbase:</b> 58.0 in (147 cm) <b>Tread width (to centerline of tire):</b> 46.9 in (119 cm)																		
<b>Width:</b>	84.0 in (213 cm)	71.5 in (182 cm)																			
<b>Overall Height:</b>	73.0 in (185 cm)	73.0 in (185 cm)																			
<b>Weight:</b>	920 lbs (417 kg)	970 lbs (439 kg)																			
<b>GROUND CLEARANCE</b>	5.5 in (14 cm) (at machine centerline 24 in tire)																				
<b>TIE DOWNS</b>	Four loops, one located on each corner of the machine.																				
<b>WARRANTY</b>	2-year limited warranty. Refer to the Operator's Manual for further details.																				
<b>SAFETY CERTIFICATIONS</b>	Certified to meet ANSI specification B71.4 - 2012 standards when equipped with weight kits supplied with attachments. Certified to meet ISO/DIS 21299 for ROPS. Engine meets all applicable emission standards per the manufacturer. Certified to meet C-Tick 2004/108/EC/EMC and the CE Machinery Directive.																				

REAR ATTACHMENTS (NOTE: Unit must always have a rear attachment installed to meet ANSI and CE specifications)	
<b>FLEX TOOTH RAKE (08716) (GOLF APPLICATIONS)</b>	<ul style="list-style-type: none"> <li>84" (213 cm) wide tooth rake with three reversible rubber trowels that will not tear bunker liners</li> <li>Convex Trowel Design is able to continuously groom a 70" (178 cm) radius surface</li> <li>Lift-in-turn design allows for continuous grooming during a zero radius turn</li> <li>Rubber trowel design reduces damage to bunker edges and liners</li> </ul>
<b>OPTIONAL ACCESSORIES FOR TOOTH RAKE</b>	Broom Finishing Kit (three section brush), Model 08719
<b>NAIL DRAG (08717) (INFIELD GROOMING APPLICATIONS)</b>	<ul style="list-style-type: none"> <li>66" (168 cm) wide with 88 removable nails arranged in diamond pattern</li> <li>3 height position for nails increases material flow and extends nail wear</li> <li>71.5" (182 cm) rubber groomer</li> <li>Back blade allows for moderate or small area leveling of infield surface</li> </ul>
<b>OPTIONAL ACCESSORIES FOR NAIL DRAG</b>	Drag mat finishing kit (08718): (78"W X 18"L 1"square steel mat); includes cradles to store mat during transport. Model 08718
OTHER TRACTION UNIT ACCESSORIES	
<b>LIGHT KIT</b>	2 LED lights, one in front one mounts to ROPS and points rearward. 3 Position switch, all lights on, front on or off. Model 08721
<b>SPEED LIMITER KIT</b>	Automatically reduces maximum speed of the traction unit when the rear attachment is lowered. Adjustable to maximum speed of 3 – 7 mph (4.8 – 11.3 km/h). Model 08720.
<b>TRANSPORT SPEED LIMITER KIT</b>	Reduces speed infinitely from top speed to approximately 7 mph (11 k/hr) or top speed of grooming speed. Part 130-7877
<b>SEAT SUSPENSION KIT</b>	Rubber isolators provide cushioning. PN 125-6469
<b>MESH BAG KIT</b>	Storage bag for maintenance tools, trash, debris, etc.; mounts to ROPS. PN 127-0359
<b>TURF TRAC TIRE</b>	Less aggressive tread for rear drive tires. PN 125-6462
<b>BIMINI SUNSHADE</b>	Canvas sunshade that mounts to ROPS. Model 30358
<b>RAKE HOLDER</b>	SP2040Z has a standard rake holder mounted on left hand side, a second optional rake holder can mount to right hand side of SP2040Z. PN 127-0353-03

\*Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. Consult your local Toro Distributor.

