

## SAFELY AND EASILY TRANSPORT ONE OR TWO WALK GREENS MOWERS.

Toro® TransPro® trailers safely and easily transport walk greens mowers to and from the mowing area.

The unique design protects your mower investment and keeps adjustments intact. The TransPro 80 accommodates a single Greensmaster® with a flat ramp or rail ramp kit. For additional time and productivity gains, transport two mowers (excluding the Greensmaster 1600 and 1026) with the TransPro 200.



TransPro 80



TransPro 200

## F E A T U R E S

### TransPro 200

- Safely transport one or two walk greens mowers
- Rail ramp module simplifies operation and reduces loading time by up to 50% – no need to mount mower transport wheels
- Adjustable roller pockets allow for configuration of fixed units and flex units, with or without groomers
- Combination of roller pocket, rubber mats and wheel/doughnut retainer securely retain mower(s) in place,

helping to keep mower adjustments intact. Once the ramp or rails are raised, units are locked in place

- Open trailer design allows for easy wash-down of the mower without unloading
- Single configuration for either 45.7 cm (18") or 53.3 cm (21") wide units
- Hitch pin release is incorporated into convenient lift handle for trailer hitch. 6.35 cm (2.5") adjustable hitch height for level trailering and loading

### TransPro 80

- Safely transport one walk greens mower
- Rail ramp simplifies operation and reduces loading time by up to 50% – no need to mount mower transport wheels
- Large trailer tyres to cushion ride and help protect mower during transport
- Rubber mat protects greens mower front rollers during transport, helping to keep mower adjustments intact

- Open design allows servicing and wash-down while mower is on the trailer
- Quick-lock device secures mower to the trailer for safe transport



	TRANSPRO 80, MODEL 04238	TRANSPRO 200, MODEL 04239
<b>LOAD CAPACITY</b>	181.6 kg (400 lb) including weight of trailer	522 kg (1,150 lb) including weight of trailer
<b>SUSPENSION</b>	Large low-pressure tyres (20 x 10-8)	
<b>TRANSPORT SPEED</b>	Maximum of 15 mph	
<b>RAMP</b>	Textured split ramp design with detented wheel retainers	Textured split ramp design with spring-loaded ramp retainers for storage during transport operation
<b>RAIL</b>	Textured loading rails for use in conjunction with smaller bogey (donut) wheels in place of transport tyres.	
<b>HITCH</b>	Pin type hitch is standard; tongue is 6.4 cm (2.5") wide and adjustable in length (will accept standard ball hitch)	6.4 cm (2.5") adjustable hitch height for level towing and loading. Pin release is incorporated into lift handle.
<b>TOWING</b>	Designed to tow behind a utility vehicle with tongue height 18-33 cm (7"-13"); maximum tongue load 25 kg (55 lb)	
<b>RETENTION METHOD</b>	Quick latch mower caddy, wheel/doughnut retainer and retention straps to maintain upright mower orientation	Adjustable front roller pockets and wheel/doughnut retainer positively secure mower for transport
<b>FINISH</b>	Rust-/corrosion-resistant paint	
<b>AXLES</b>	Heavy-duty stub. Can be greased	Heavy-duty stub. Maintenance-free sealed bearings.
<b>DIMENSIONS</b>	Height: 48.3 cm (19") Width: 157.5 cm (62") Length: 205.7 cm (81")	Height: 154.9 cm (61") Width: 172.7 cm (68") Length: 274 cm (108")
<b>TRAILER WEIGHT</b>	Ramp configuration: 67 kg (147 lb) rail configuration: 62 kg (136 lb)	Ramp configuration: 176 kg (389 lb) rail configuration: 149 kg (329 lb)
	Easily adjustable to fit all Toro walk greens mowers. (optional axle kit may be required)	Easily adjustable to fit all 45.7 cm (18") and 53.3 cm (21") Toro walk greens mowers. (not recommended for Greensmaster® 1600 or 1026)

TRANSPRO 80 ACCESSORIES	TRANSPRO 200 ACCESSORIES
04245 Flat ramp kit	04219 Wheel loading kit
04247 Rail ramp kit	04229 Rail loading kit
107-8188 Hitch kit	144-5668 Axle kit – Greensmaster Flex18/21
136-7287 Extended axle for rail ramp using 04648 groomer for Flex18XX/21XX units	144-5664 Axle kit – Greensmaster Flex 18XX/21XX
139-6478 Extended axle shaft – 1018/1021/1026 fixed head units with groomer	144-5663 Axle kit – Greensmaster 800/1000 series
139-2732 Extended axle shaft – 1018/1021 Flex head units with groomer	

\* Specifications and design subject to change without notice. Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. Consult your local Toro Distributor.

Rev. 1/23



**toro.com**

Worldwide Headquarters  
The Toro Company  
8111 Lyndale Ave. So.  
Bloomington, MN 55420 USA  
Phone: +(1) 952 888 8801

©2023 The Toro Company.  
All rights reserved.  
23-238-GB



facebook.com  
twitter.com/TheToroCompany  
youtube.com/ToroCompanyEurope



**Count on it.**